

MATERIAL SAFETY DATA SHEET

PALMER ASPHALT COMPANY

Telephone: (201) 339-0855

Manufacturer: Palmer Asphalt Company
Address: 196 West 5th Street, P.O. Box 58
Bayonne, NJ 07002

Emergencies: 201-339-0855
8:00 a.m. - 5:00 p.m. EST

After Hours Call: CHEMTREC:
800-424-9300 (Domestic - No. America)
703-527-3887 (International)

Quick Identifier: Bulldog Gravel Polyester

MSDS Number: 47

Issue Date: February 10, 1990

Date Prepared: Rev. April 13, 2006

Prepared By: PRI Asphalt Technologies, Inc.

SECTION 1 - PRODUCTS FOR WHICH THIS MSDS APPLIES

- Polyester Stitchbond, Warpknit, or Woven Fabrics heat set only.
- Polyester / Cellulosic fabric blends heat set only.
- Any of the above which have been disperse dyed or printed.
- Any of the above finished with a napping softener and/or fluorochemical finish.

SECTION 2 - HAZARD INGREDIENTS

There are no hazardous ingredients as defined in 29 CFR Part 1910.1200 which require listing.

SECTION 3 - PHYSICAL DATA

Most physical data (such as vapor pressure and flash point) applicable to chemicals does not apply to the above products.

Polyester Melt Point: Approximately 490°F. Cellulosics burn and do not melt.

SECTION 4 - HEALTH HAZARD DATA

Exposure to fabrics described in this MSDS should pose no health risks or problems during normal conditions of use.

SECTION 5 - FIRE / COMBUSTION PRODUCTS

Polyester fabrics will melt at approximately 500°F and cellulosics will readily burn when exposed to flame. Combustion and decomposition gases and products may consist of carbon, hydrogen, oxygen and nitrogen in various combinations. Fire fighters should take precautions against breathing combustion gases. Molten polyester can cause severe burns to the skin.

SECTION 6 - SAFETY AND CONTROL MEASURES

Customary personal hygiene measures such as washing hands after working with fabrics are recommended. Adequately ventilated work spaces are recommended. Avoid breathing any dust that may evolve during processing.

SECTION 7 - EMERGENCY AND FIRST AID

No problems are anticipated from normal exposure to fabrics represented by this MSDS. However, should exposure result in skin, eye, or respiratory tract irritation, the affected individual should be removed from the area of exposure and be provided appropriate medical attention.

For Other Product Information Contact:

**PALMER ASPHALT COMPANY
P.O. BOX 58
BAYONNE, NJ 07002
TELEPHONE: (201) 339-0855
FAX: (201) 339-8320**

*** SINCE 1932 ***

**MANUFACTURERS OF BULLDOG AND PRIVATE LABEL COLD-APPLIED
COATINGS AND CEMENTS**