



MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

Product: BULLDOG/DUREX #BC 123 Elastomeric Coating- Base Coat

Product Code: BC123

MSDS Date: 06-01-08

2. COMPANY IDENTIFICATION

Palmer Asphalt Company

196 West 5th Street

Bayonne, NJ 07002

Emergency Phone # 201-339-0855 (8:00 am - 5:00 pm EST)

After Hours Call: CHEMTREC

800-424-9300 (Domestic - No. America)

703-527-3887 (International)

3. INGREDIENTS

#	Ingredient	CAS Reg. #	Weight (%)	Vapor Pressure mm Hg @ Temp	Occupational Exposure Limits
1	Aqua Ammonia	1336-21-6	<1.00	755.00 @ 80°F	ACGIH TWA 25 ppm
2	Propylene Glycol	57-55-6	1 – 5	1.00 @ 77°F	None established
3	Acrylic Polymers	NA	15 – 25	NA	NA
4	Calcium Carbonate	1317-65-3	30 – 40	NA	10 mg/m ³ (dust)
5	Zinc Oxide	1314-13-2	1 – 5	NA	10 mg/m ³ (dust)
6	Titanium Dioxide	13463-67-7	5 – 10	NA	10 mg/m ³ (dust)
7	Iron Oxide Black	12227-89-3	<1.00	NA	10 mg/m ³ (dust)
8	Petroleum Based Defoamer	Proprietary	<1.00	NA	5 mg /m ³ TWA
9	Hydroxyethylcellulose	9004-62-0	<2.00	NA	None established
10	Water	7732-18-5	30 – 35	760.00 mm Hg @ 68°F	NA
11	Ester-Alcohol	25265-77-4	<2.00	<.01 mmHg @ 20°C	None established

Proposition 65 Statement: Certain raw materials used in making this product may contain small amounts of materials as impurities which are regulated by Propostion 65.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Semi viscous liquid
State	Liquid
Odor Characteristic	Mild ammonia odor
Vapor Density (Air = 1)	Heavier than air
Vapor Pressure	No data
Weight per gallon	11.5 – 12.5
Boiling Point	250 ⁰ F
Solubility in Water	Soluble
VOC	<100 grams/liter
Evaporation Rate	Slower than ether

The physical and chemical data given in Section 4 are typical values for this product and are not intended to be product specifications.

5. FIRE AND EXPLOSION HAZARD DATA

Flash Point	Non-Combustible
-------------	-----------------

Extinguishing agents: Foam, CO₂, Dry Chemical, Water fog

Personal Protective Equipment: As in any fire, wear self-contained breathing apparatus (pressure-demand, NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards: Pressure may build up in tightly closed containers exposed to fire which may result in rupture. Keep containers cooled with water spray. Material can spatter above 100°C/212°F.

6. REACTIVITY DATA

Instability: Material is considered stable. However, avoid temperatures above 177°C/350°F the onset of polymer decomposition. Thermal decomposition is dependent on time & temperature.

Hazardous Decomposition Products: Thermal decomposition may yield acrylic monomers.

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Incompatibility: None known

7. HEALTH HAZARD DATA

Primary Routes of Exposure: Inhalation - Skin Contact - Eye Contact

Inhalation - Inhalation of vapor or mist can cause the following: irritation of nose, throat and lungs

Eye Contact - Material can cause the following: -slightly irritating to the eyes.

Skin Contact - Prolonged or repeated skin contact can cause the following: -moderate skin irritation – reddening

Ingestion - Material is harmful if swallowed. Material can cause the following:-gastrointestinal irritation – nausea – vomiting – diarrhea

8. FIRST AID MEASURES

Inhalation - Move subject to fresh air. If breathing is difficult, give oxygen. Give artificial respiration if breathing has stopped. Get medical attention immediately.

Eye Contact - Immediately flush eyes with a large amount of water for at least 15 minutes. If redness, itching or a burning sensation develops, see a physician.

Skin Contact - Remove contaminated clothing. Wash affected areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse. If redness, itching or a burning sensation develops, see a physician.

Ingestion - DO NOT induce vomiting. Give milk or water to drink. Get medical attention immediately. If vomiting occurs spontaneously, keep airway clear.

Note to Physician - No specific antidote, treat symptomatically.

9. ACCIDENTAL RELEASE MEASURES

Personal Protection: Wear compatible, chemically resistant gloves. Wear protective clothing including splash proof goggles and rubber overshoes.

Procedures: Contain spills immediately with inert materials (e.g. sand, earth). If material is spilled in a confined area ventilate the area well. Keep spectators away. Floor may be slippery; use care to avoid falling. Transfer liquids and solid diking material to separate suitable containers for recovery or disposal. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

10. HANDLING & STORAGE

Storage Conditions: Avoid temperature extremes during storage; ambient temperature preferred. Store in well-ventilated area. Keep container tightly closed when not in use. Keep from freezing. Store material out of direct sun.

Handling Procedures: Use in well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames. Do not work alone! Keep out of reach of children!

Other: Improper disposal or re-use of this container may be dangerous and illegal. Refer to applicable local, state and federal regulations.

11. EXPOSURE CONTROLS – PERSONAL PROTECTION

Respiratory Protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operation conditions. Approved mechanical filter respirator to remove solid airborne particles of overspray during spray application.

Eye Protection: Use chemical splash goggles or face shield. (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed.

Hand Protection: Chemical-resistant gloves should be worn whenever this material is handled. Rinse and remove gloves immediately after use. Wash hands with soap and water.

Other protection: Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact.

Engineering Controls (Ventilation): Use local exhaust ventilation with a minimum capture velocity of 100ft/min. (.5 m/sec.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Work – Hygienic Practices: Remove contaminated clothing; launder or dry clean before reuse. Wash thoroughly with soap and water.

12. DISPOSAL CONSIDERATIONS

Procedure: Dispose of in accordance with local, state and federal regulations.

13. TRANSPORT INFORMATION

US DOT Class	Paint, Not regulated
--------------	----------------------

14. OTHER INFORMATION

Category	HMIS – BC123	Scale
Toxicity	1	4=Extreme
Fire	0	3=High
Reactivity	0	2=Moderate
Special	-	1=Slight
		0=Insignificant

Prepared by: Palmer Asphalt Company – Technical Department

The information contained herein relates only to the specific material identified. Palmer Asphalt Company believes that such information is accurate and reliable as of the date of this Material Safety Data Sheet, but no representation, guarantee or warranty, expressed or implied, is made as to the accuracy, reliability, or completeness of the information. Since conditions of use are out of our control, users assume all risks associated with the use of the material and are advised to confirm in advance that the information contained in this MSDS is correct, applicable, and suitable to their circumstances. As these are proprietary formulations, the actual percentages of ingredients have been omitted pursuant to OSHA Federal Hazard Communication Standard.

PALMER ASPHALT COMPANY
196 WEST 5TH STREET
BAYONNE, NJ 07002
www.palmerasphalt.com

