

#93AF BULLDOG® COAL TAR ROOF RESATURANT

DESCRIPTION

A fibered coal tar coating enhanced by penetrants that help it rejuvenate badly deteriorating coal tar roofs. Part of this compound soaks into dried out roofing felts and part of it remains on the surface to provide water/weather proof protection.

SPECIFICATIONS: Federal Specification *SS-C-540-B
*Exception Non-Asbestos

USES

Use when coal tar felts have dried as a result of unprotected exposure to sun's destructive rays. Sometimes used to restore roof, rather than remove it. **This material has a strong odor. Cover air intakes until material dries or avoid using near air intakes.**

Do not use on asphalt surfaces.

For exterior use only.

METHOD and RATE OF APPLICATION

Apply with roof brush or spray equipment to dry, sound, clean surface. Remove loose gravel. Depending on condition of surface apply at rate of 7 to 8 gallons per 100 square feet (2.8 to 3.2 liters per M2). If removing existing gravel is desired do so with power brush or other suitable means that will not damage underlying felts. If gravel is to be reused power wash before reusing to remove silt. Reapply gravel immediately after applying Resaturant. Be certain roof can support additional weight.
COVER AIR INTAKES BEFORE APPLYING AND WHILE CURING.

CONTAINER SIZE

55 Gallon Drum

5 Gallon Pail

APPROXIMATE SHIPPING WEIGHTS

590 POUNDS

54 POUNDS

TYPICAL PHYSICAL CHARACTERISTICS

Mineral Filler and/or other Stabilizers, % by Weight	4.0
Solids, % by Weight	87
Water Content, % by Volume	0.5 max
Net Weight Per Gallon	9.1 lbs
Dry Film Thickness Without Absorption Applied at Rate of 100 Square Feet Per Gallon	15 Mils
Flash Point, in Degrees F., C.C., ASTM D 93	105 Minimum
Condition in Container	May Require Slight Stirring
Clean-up of Tools	O.S.H.A. Approved Solvent
Clean-up of Skin	Waterless Hand Cleaner

Copyright © Palmer Asphalt Company

3-07

The typical characteristics shown for this product are based upon the average of test results conducted on the finished product and on the raw material components used. They are subject to production variations and may be changed without notice. All other information contained on this sheet is to be used as a guide. For proper use and application please observe instructions and cautions on container.

DISCLAIMER OF WARRANTIES . The application procedures and other information contained herein or on any other literature or on the labels of any of our products is intended to provide a guide for the general use, handling, and storage of products produced by Palmer Asphalt Company and is based upon ideas that are well tested and believed to be reliable. Palmer Asphalt Company hereby disclaims all warranties, either expressed or implied, since it cannot control workmanship, weather, quality of other materials used, and other variables that might affect the results. Liability under this warranty is limited to the replacement of our material or refund of its cost at our option. This Company does not authorize any agent or any representative to make any warranty.

PALMER ASPHALT COMPANY
196 WEST 5th STREET
P.O. BOX 58
BAYONNE, NJ 07002
(201) 339-0855